

1 What is claimed is:

2 1. A method for objective measurement of video quality using a wavelet transform,
3 comprising:

4 a 2-dimensional wavelet transform that is applied to each frame of a source video and
5 each frame of a processed video, producing source video wavelet coefficients for each
6 frame of said source video and processed video wavelet coefficients for each frame of
7 said processed video;

8 difference computing means that computes a subband difference in each subband block
9 by summing differences between said source video wavelet coefficients and said
10 processed video wavelet coefficients in each subband block of said 2-dimensional
11 wavelet transform and represents subband differences as a difference vector for each
12 frame, producing a sequence of difference vectors for said source video and said
13 processed video;

14 combining means that combines said sequence of difference vectors and produces a final
15 difference vector; and

16 weighting means that produces a number, which is used as an objective score for
17 objective measurement of video quality, by calculating a weighted sum of the elements
18 of said final difference vector.

19
20 2. A method for objective measurement of video quality using a modified 3-dimensional
21 wavelet transform, comprising:

22 a 2-dimensional wavelet transform that is applied to each frame of a source video and
23 each frame of a processed video, producing source video wavelet coefficients for each
24 frame of said source video and processed video wavelet coefficients for each frame of
25 said processed video;

1 difference computing means that computes a subband difference in each subband block
2 by summing differences between said source video wavelet coefficients and said
3 processed video wavelet coefficients in each subband block of said 2-dimensional
4 wavelet transform and represents subband differences as a difference vector for each
5 frame, producing a sequence of difference vectors for said source video and said
6 processed video;

7 a 1-dimensional wavelet transform that is applied to said sequence of difference vectors
8 in a temporal direction, producing a second sequence of difference vectors;

9 combining means that combines said second sequence of difference vectors and produces
10 a final difference vector; and

11 weighting means that produces a number, which is used as an objective score for
12 objective measurement of video quality, by calculating a weighted sum of the elements
13 of said final difference vector.

- 14 3. A optimization method that finds the best linear combination of various parameters that
15 are obtained for objective measurement of video quality, comprising:

16 a plurality of subjective scores that are represented as a random variable x ;

17 a plurality of objective parameter vectors that are represented as a random vector D ;

18 eigenvector computing means that computes the eigenvectors of $\Sigma_D^{-1} \Sigma_Q$ where Σ_D is the
19 covariance matrix of said objective parameter vectors, $\Sigma_Q = QQ^T$, and $Q = E(xD)$;

20 optimal weight selecting means that selects, from the eigenvectors of $\Sigma_D^{-1} \Sigma_Q$, the
21 eigenvector that corresponds to the largest eigenvalue of $\Sigma_D^{-1} \Sigma_Q$ as an optimal weight
22 vector W_{opt} ; and

1 objective score producing means that produces a number, which is used as an objective
2 score for objective measurement of video quality, by computing $W_{opt}^T V_p$ where V_p is an
3 objective parameter vector.

4 4. A method for objective measurement of video quality using spatial and temporal
5 frequency differences, comprising:

6 frequency difference computing means that computes spatial and temporal frequency
7 differences between a source video and a processed video, producing a frequency
8 difference vector for said source video and said processed video;

9 weighting means that produces a number, which is used as an objective score for
10 objective measurement of video quality, by calculating a weighted sum of the elements
11 of said frequency difference vector.

12 5. The method in accordance with claim 4 wherein said frequency difference computing
13 means applies a transform to said source video and said processed video and computes
14 coefficient differences, producing said frequency difference vector.



Chulhee Lee

February 23, 2002